

Product description

Glasliner® is a plastic laminate, flat and opaque that solves the highest requirements for coating, protecting and decorating at a low cost.

Application

- Manufacture of agricultural panel for covers



Advantage

- **Hygiene:** Its composition ensures an aseptic coating. Resistant to moisture and not forming fungi or bacteria
- **Low maintenance:** 100% washable, easy to clean and no external paint requirement.
- **Economy:** Ease of installation that implies savings in time. Investment at low cost.

Technical characteristics

| Properties | Rule | Value |
|---|--------------|-----------------------------|
| Thickness | - | 0,6 mm |
| Coefficient of linear thermal expansion | ASTM D-696 | $2,7 \times 10^{-3}$ cm/m°C |
| Thermal conductivity (K) | ASTM C-177 | 0,4 W/m °K |
| Tensile strength | EN ISO 527-4 | 50 MPa |
| Young's modulus | EN ISO 527-4 | 6300 MPa |
| Reaction to fire | EN 13501-1 | F |

Standard product specifications

- Thickness: $\pm 10\%$
- Width and length: ± 3 mm (sheets)
- Squareness: ≤ 3 mm

The information referred to in this Technical Data Sheet is based on the experience and the tests carried out by the company, without this implying any kind of responsibility for its different applications, given that Stabilit Europa does not have any kind of control over its final use.