



## TECHNICAL DATA

**Glasliner 1,0 mm**  
Smooth opaque sheet

Code: TDS-GD-GC-10

Inspection: 00

Valid from : 16/04/18

Page : 1 of 1

### Product description

Glasliner® is a plastic laminate, flat and opaque that solves the highest requirements for coating, protecting and decorating at a low cost.

### Application

- **Industrial:** Chemical plants, food processing
- **Commercial:** Supermarkets, kitchens, restaurants offices, cold rooms, freezers.
- **Health:** Hospitals, laboratories, pharmacies.
- **Residential:** Bathrooms, kitchens, laundries.
- **Institutional:** Schools, museums

### Advantage

- **Hygiene:** Its composition ensures an aseptic coating. Resistant to moisture and not forming fungi or bacteria
- **Low maintenance:** 100% washable, easy to clean and no external paint requirement.
- **Economy:** Ease of installation that implies savings in time. Investment at low cost.

### Technical characteristics

Properties	Rule	Value
Thickness	-	1,0 mm
Coefficient of linear thermal expansion	ASTM D-696	$2,7 \times 10^{-3}$ cm/m°C
Thermal conductivity (K)	ASTM C-177	0,4 W/m °K
Tensile strength	EN ISO 527-4	45 MPa
Flexural strength	EN 14125	64 MPa
Barcol hardness	EN 59	30-40

### Standard product specifications

- Thickness:  $\pm 10\%$
- Width:  $\pm 3$  mm
- Length:  $\pm 3$  mm (en lámina)
- Squareness:  $\leq 3$  mm

The information referred to in this Technical Data Sheet is based on the experience and the tests carried out by the company, without this implying any kind of responsibility for its different applications, given that Stabilit Europa does not have any kind of control over its final use..