

## Product description

Glasliner® is a plastic laminate, flat and opaque that solves the highest requirements for coating, protecting and decorating at a low cost.

## Application

- **Industrial:** Chemical plants, food processing industry
- **Commercial:** Supermarkets, kitchens, restaurants, offices, cold rooms, freezers.
- **Health:** Hospitals, laboratories, pharmacies.
- **Residential:** Bathrooms, kitchens, wash laundries.
- **Institutional:** Schools, museums.

## Advantages

- **Hygiene:** Its composition ensures an aseptic coating. Resistant to moisture and not forming fungi or bacteria
- **Low maintenance:** 100% washable, easy to clean and no external paint requirement
- **Economy:** Easy to install that implies savings in time. Investment at low cost.

## Technical characteristics

Properties	Norm	Value
Thickness	-	3,0 mm
Coefficient of lineal thermal expansion	ASTM D-696	$2,7 \times 10^{-3}$ cm/m°C
Thermal conductivity (K)	ASTM C-177	0,4 W/m °K
Tensile strenght	EN ISO 527-4	70 MPa
Flexural strenght	EN 14125	110 MPa
Barcol Hardness	EN 59	30-40
Reaction to fire	EN 13501-1	E

## Standard product specifications

- Thickness:  $\pm 10\%$
- Width:  $\pm 3$  mm
- Length:  $\pm 3$  mm (in sheet)
- Squareness:  $\leq 3$  mm

## Standard product specifications

- Reaction to fire certificate according to EN 13501-1. Classification Obtained: E

Warranty is limited to replacement of damaged blades. In this case, the new sheets will be delivered by the manufacturer free of charge. The manufacturer's liability does not include any costs for removal and installation of the sheets.

The information referred to in this Technical Data Sheet is based on the experience and tests carried out by the company, without this implying any type of responsibility for its different applications, given that Stabilit Europa has no type of control over its final use.

