

## Product Description

Glasliner® is a flat and opaque plastic laminate that solves the highest requirements for coating, protecting and decorating at a low cost. They are designed to provide durability and easy cleaning and maintenance.

## Application

- **Industrial:** Chemical plants, food processing.
- **Commercial:** Supermarkets, kitchens, restaurants offices, cold rooms, freezers.
- **Health:** Hospitals, laboratories, pharmacies.
- **Residential:** Bathrooms, kitchens, laundries.
- **Institutional:** Schools, museums.

## Advantages

- **Hygiene:** Its composition ensures an aseptic coating. Resistant to moisture and not forming fungi or bacteria.
- **Low Maintenance:** 100% washable, easy to clean and no external painting requirement.
- **Economy:** Ease of installation that implies savings in time.

## Technical Properties

Properties	Standard	Unit
Thickness	-	3.0 mm
Coefficient of Linear Thermal Expansion	ASTM D696	$2,7 \times 10^{-3}$ cm/m °C
Tensile Strength	EN ISO 527-4	55 MPa
Tensile Modulus	EN ISO 527-4	5.600 MPa
Flexural Strength	EN 14125	95 MPa
Flexural Modulus	EN 14125	1.118 MPa
Barcol Hardness	EN 59	30 - 40
Water Absorption	ASTM D-570	0,3 %

## Specifications and Certifications:

- Stabilit Europe distinguishes itself by having the certification of the Quality Management System according to ISO 9001 in all its processes.
- Certificate Reaction to fire according to EN 13501-1. Classification obtained: E

Warranty is limited to replacement of damaged blades. In this case, the new sheets will be delivered by the manufacturer free of charge. The manufacturer's liability does not include any costs for removal and installation of the sheets.

The information referred to in this Technical Data Sheet is based on the experience and tests carried out by the company, without this implying any type of responsibility for its different applications, given that Stabilit Europa has no type of control over its final use.